

| Model Name | Type | Resolution | Image Sensor | WDR | Sens-up (DSS) | DNR | PCB Size | Power Range | OSD Access | Lens Holder | IRIS | Stepping AF 2-Motor Lens | IR-Cut Removal (LED Sync/Control) | Other simultaneous video output | Audio I/O | Alarm I/O | RS485 bypass | SD Card | O/S | Etc. [Status] | |
|-----------------|----------|-------------|---|---------------------------------------|---------------|-----|---------------------|--------------------------|---|----------------|----------------------|--------------------------|-----------------------------------|---------------------------------|----------------------|-------------------|--------------|-----------|---------------------|---------------------|--|
| | | | | Only one of the three can be selected | | | | | | | | | | | | | | | | | |
| DCC-1A0 | IP H.264 | 1080P 25/30 | Sony 1/2.8" IMX327LQR | Yes* <i>(Double Scanned WDR)</i> | Yes (X32)* | 3D* | 28x28mm Type 1-B/D | DC12V±10% POE (Option) | HTTP Webpage . Via Network API(Protocol) | X | Fixed IRIS | X | X | X | X | X | X | X | X | RTOS Dual Streaming | Mini-Box Housing (30x30mm) [Mass Production] |
| DCC-1H0 | IP H.264 | 1080P 25/30 | Sony 1/2.8" IMX327LQR | Yes* <i>(Double Scanned WDR)</i> | Yes (X32)* | 3D* | Ø17 & Etc. 3-B/Ds | DC12V±10% POE (Option) | HTTP Webpage . Via Network API(Protocol) | X | Fixed IRIS | X | X | X | X | X | X | X | X | RTOS Dual Streaming | Mini-Bullet Housing (Ø19) [Mass Production] |
| DCC-1H1 | IP H.264 | 1080P 25/30 | Sony 1/2.8" IMX327LQR | Yes* <i>(Double Scanned WDR)</i> | Yes (X32)* | 3D* | Ø17 & Etc. 3-B/Ds | DC5-12V±10% POE (Option) | HTTP Webpage . Via Network API(Protocol) | X | Fixed IRIS | X | X | X | X | X | X | X | X | RTOS Dual Streaming | Mini-Bullet Housing (Ø19) [Mass Production] |
| DCC-1K0 | IP H.264 | 1080P 25/30 | Sony 1/2.8" IMX327LQR | Yes* <i>(Double Scanned WDR)</i> | Yes (X32)* | 3D* | 32x32mm 1-B/D | DC12V±10% POE (Option) | HTTP Webpage . Via Network API(Protocol) | M12, D14, C/CS | Fixed IRIS | X | X | X | Input Only | X | X | X | X | RTOS Dual Streaming | [Mass Production] |
| DCC-1M0 | IP H.264 | 1080P 25/30 | Sony 1/2.8" IMX327LQR | Yes* <i>(Double Scanned WDR)</i> | Yes (X32)* | 3D* | 42x42mm 1-B/D | DC12V±10% POE (Option) | HTTP Webpage . Via Network API(Protocol) | M12, D14, C/CS | DC Auto & Fixed IRIS | O | O | X | In / Out*** (Option) | 2 / 1*** (Option) | Option*** | Option*** | RTOS Dual Streaming | [Mass Production] | |
| DCC-2C0 | IP H.264 | 1080P 25/30 | Sony 1/2.8" IMX327LQR | Yes* <i>(Double Scanned WDR)</i> | Yes (X32)* | 3D* | Ø17 & Etc. 3-B/Ds | DC12V±10% POE (Option) | HTTP Webpage . Via Network API(Protocol) | X | Fixed IRIS | X | X | X | In / Out | X | X | X | X | RTOS Dual Streaming | Mini-Bullet Housing (Ø19) [Mass Production] |
| DCC-2T0 | IP H.264 | 1080P 25/30 | Sony 1/2.8" IMX327LQR | Yes* <i>(Double Scanned WDR)</i> | Yes (X32)* | 3D* | 26x22mm Type 2-B/Ds | DC5V±10% POE (Option) | HTTP Webpage . Via Network API(Protocol) | X | Fixed IRIS | X | X | X | X | X | X | X | X | RTOS Dual Streaming | [Mass Production] |
| DCC-960 | IP H.264 | 1080P 25/30 | Sony 1/2.8" IMX327LQR | Yes* <i>(Double Scanned WDR)</i> | Yes (X32)* | 3D* | 32x32mm 1-B/D | DC12V±10% POE (Option) | HTTP Webpage . Via Network API(Protocol) | M12, D14, C/CS | Fixed IRIS | X | O | X | X | X | X | X | X | RTOS Dual Streaming | [Mass Production] |
| DCC-2W30 | IP H.264 | 1080P 25/30 | Sony 1/2.8" IMX327LQR | Yes <i>(Double Scanned WDR)</i> | Yes (X32) | 3D | 42x42mm 2-B/Ds | DC12V±10% POE (Option) | HTTP Webpage . Via Network API(Protocol) | M12, D14, C/CS | DC Auto & Fixed IRIS | O | O | SDI and (CVBS/AHD/TVI)** | In / Out | 2 / 1 | O | O | RTOS Dual Streaming | [Mass Production] | |
| DCC-1Z30 | IP H.264 | 1080P 25/30 | Sony 1/2" IMX385LQR | Yes <i>(Double Scanned WDR)</i> | Yes (X32) | 3D | 42x42mm 2-B/Ds | DC12V±10% POE (Option) | HTTP Webpage . Via Network API(Protocol) | M12, D14, C/CS | DC Auto & Fixed IRIS | O | O | SDI and (CVBS/AHD/TVI)** | In / Out | 2 / 1 | O | O | RTOS Dual Streaming | [Mass Production] | |
| DCC-2S30 | IP H.264 | 1080P 25/30 | Sony 1/2.3" IMX392LQR Global Shutter | Yes <i>(Double Scanned WDR)</i> | Yes (X32) | 3D | 42x42mm 2-B/Ds | DC12V±10% POE (Option) | HTTP Webpage . Via Network API(Protocol) | M12, D14, C/CS | DC Auto & Fixed IRIS | O | O | SDI and (CVBS/AHD/TVI)** | In / Out | 2 / 1 | O | O | RTOS Dual Streaming | [Mass Production] | |
| | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | |
| New | | | | | | | | | | | | | | | | | | | | | |

*: Due to internal memory issues, you cannot select all three features at the same time: WDR, 3D-NR, and DSS. You can only select one of the three.
For boards such as the DCC-2S30, all three functions can be selected simultaneously.

** : Select one to out

*** : DCA-IPSub Board is required.

